Three Fan Controller

BLUE GIANT®

Key Features

- · Easily mounted to wall
- Control each fan individually
- 100' (30.48 meters) of 6-core cable for installation supplied by Blue Giant
- Operates fan in either forward (cooling) or reverse (destratification)
- Manually control the speed of each fan

Technical Specifications


| AutoPilot Controller Specifications | | | | |
|-------------------------------------|---|--------|--------|--------|
| Potentionmeter | 0-10V DC analog | | | |
| | 1000 ohm resistance | | | |
| | 0.5W Power consumption | | | |
| | IP66 Protection | | | |
| Connections | Control internals are factory pre-wired | | | |
| | Three (3) 100' of 6-core shielded wire supplied | | | |
| | Three (3) strain relief bushing supplied | | | |
| 3-Position Switch | FORWARD - OFF - REVERSE capability | | | |
| Enclosure | NEMA Type 12 | | | |
| | Steel enclosure | | | |
| | Gray polyester powder finish | | | |
| | Dimensions | H | W | D |
| | | 8.5" | 5" | 4.25" |
| | | 216 mm | 127 mm | 108 mm |

Certification





Wiring Diagram - Remote Switchbox



⁻⁻⁻⁻ Grounded remote control connection by installer.



Corporate 85 Heart Lake Road South Brampton, ON, Canada L6W 3K2 t 905.457.3900 f 905.457.2313 USA 6350 Burnt Poplar Road Greensboro, NC 27409 www.BlueGiant.com AUTHORIZED DEALER

Blue Giant offers a full line of dock levelers, dock safety equipment, seals and shelters, accessories, ergonomic and scissor lift equipment and industrial trucks. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact Blue Giant for latest information. Some features illustrated may be optional in certain market areas.