



85 Heart Lake Road South
 Brampton, Ontario, Canada L6W 3K2
 Phone: 905-457-3900 Fax: 905-457-2313

BLUE GIANT EQUIPMENT CORPORATION

'C' SERIES DOCK LEVELER
MODEL 'FHC' – HYDRAULIC
SPECIFICATIONS:

Dock Leveler shall be hydraulic Model _____ comes complete with hydraulic lip and deck cylinders and 4" (101mm) maintained deck tilt as manufactured by BLUE GIANT.

MODEL SIZE REF	DECK WIDTH	DECK LENGTH w/ 16" LIP	PIT DEPTH Front 20" and Rear 19 1/2"	
			PIT WIDTH	PIT LENGTH
FHC6-6	72"	75 1/2"	74"	61 1/4"
FHC6-8	72"	99 1/2"	74"	85 1/4"
FHC66-6	78"	75 1/2"	80"	61 1/4"
FHC66-8	78"	99 1/2"	80"	85 1/4"
FHC7-6	83"	75 1/2"	85"	61 1/4"
FHC7-8	83"	99 1/2"	85"	85 1/4"
Capacities available: 25,000 / 30,000 / 35,000lb				

For metric conversion to mm, multiply inches by 25.4. For conversion to kg, divide lb by 2.2.

TYPE:

Recessed, pit installed hinged dock leveler. Electro-hydraulic operated.

FUNCTION:

Vertical Travel: Working range of 12" (305mm) above and 12" (305mm) below dock level.

Automatic Vertical Compensation: Unit provides float of 12" (305mm) above and 12" (305mm) below dock level.

Automatic Lateral Compensation: Provides maintained side-to-side deck tilt of up to 4" (101mm) to compensate for canted truck beds.

Lip Operation: Hydraulically powered lip. Lip will yield under impact of incoming truck and will automatically drop pendant upon truck's departure. The length of the lip extension shall not be less than 16" (400mm) from the ramp edge.

OPERATION:

Hydraulic Operating System: Easy to operate, quiet and smooth cycling. Electro-hydraulic raising and hydraulic lowering of the dock leveler controlled from a remote single pushbutton station. Includes means of lowering the dock leveler below platform level. The loaded ramp's free fall is limited to not over 3" (76mm) by a hydraulic velocity fuse. Unit shall come complete with a 1HP motor and equipped with overload protection. Power pack mounted underneath the deck.

Remote mount push-button control station: Provide a single operation push button control station with constant pressure " I " (UP) button. Control station is NEMA4X(IP65) rated, 3-1/2" W x 7-1/4" L x 5-1/4" D (88 x 184 x 133mm) in size.

RATED CAPACITY:

Welding procedure compliant with A.W.S.D1.1 98 specifications. All units rated in compliance with ANSI MH14.1. UL approved electrical components. Standard capacities available 25,000lb to 35,000lb (11,363kg to 15,909kg). Structural deck support to include minimum six each high tensile formed channel steel box beam.

SAFETY DEVICES:

- Full operating range metal toe guard protection
- Hydraulic velocity fuse "fall safe" to limit free fall up to 3" (76mm)
- Cross traffic support - lip engaged in saddles
- Corner safety stops
- Telescopic v-grooved maintenance strut, integral to unit
- Chamfered lip

FINISH AND COLOR:

Toe guards painted safety yellow as specified by ANSI Z535.1. Remainder of unit painted blue. High visibility OSHA safety striping on stationary side toe guards.

WARRANTY:

Warranties are subject to standard limitations on liability. Please consult Blue Giant warranties at <http://www.BlueGiant.com> for full details on warranty information and product registration.

STANDARD ACCESSORIES:

- Night Locks
- Two model DB411 laminated bumpers 14"W x 10"H x 4.5"D (355 x 254 x 114mm)



85 Heart Lake Road South
Brampton, Ontario, Canada L6W 3K2
Phone: 905-457-3900 Fax: 905-457-2313

B L U E G I A N T E Q U I P M E N T C O R P O R A T I O N

MODEL 'FHC' – HYDRAULIC

OPTIONAL ACCESSORIES:

- Foam insulation underside of deck
- Side and rear rubber style weather seals
- Side and rear nylon brush weather seals
- 18" and 20" (457 and 508mm) long lips
- Remote mounted power pack on 24' (7,315mm) hydraulic hose
- Automatic dock leveler return to cross traffic position
- Pour-in pan (dock leveler welded to a steel pan, allowing it to be "poured in place" after concrete slab is poured)
- Clean pit frame
- Specify power supply voltage
- Vehicle restraint to keep trailer securely stationed at the loading dock