

## MAST SPECIFICATIONS

MODEL	LIFT	FREE LIFT	STAGES	MINIMUM STRADDLE I.D.	LOWERED MAST HEIGHT	RAISED MAST HEIGHT
—	H3	H2	—	H1	H4	H4
<b>BGS-15</b>	52"	52"	1	31"	72"	72"
<b>BGS-22/30</b>	52"	52"	1	31"	71.25"	71.25"
<b>BGS-15</b>	72"	72"	1	31"	92"	92"
<b>BGS-22/30</b>	72"	72"	1	31"	91.25"	91.25"
<b>BGS-15</b>	90"	23"	2	31"	72"	108.75"
<b>BGS-22/30</b>	90"	11"	2	31"	65.25"	109"
<b>BGS-15</b>	110"	23"	2	31"	82"	128.75"
<b>BGS-22/30</b>	110"	11"	2	31"	75.25"	129"
<b>BGS-15</b>	130"	23"	2	33"	92"	148.75"
<b>BGS-22/30</b>	130"	11"	2	33"	85.25"	149"
<b>BGS-15</b>	150"	23"	2	38"	102"	168.75"
<b>BGS-22/30</b>	150" *	11"	2	38"	95.25"	169"

\* 3,000 lb model, downrated to 2,200 lb capacity above 130" lift