IN-PLANT LIFT TABLES



Hydraulic Tilters

Blue Giant Hydraulic Tilters come with a standard 8" or 12" (203 x 305 mm) lowered height depending on the tilt angle, and a standard base and platform of 36" x 48" (914 x 1,219 mm) (maximum platform size available is 48" x 60"). They also have an easily accessible internal power unit, as well as lifetime lubricated bushings at all pivot points. Oversized and custom sizes are available as well.

FEATURES

- 8" lip standard
- · Easily accessible internal power units
- Heavy-duty cylinders
- Lifetime lubricated bearings
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- Customized lips
- External power unit
- Floor stands
- Foot pedal control
- Oversized platform
- PLC controlled
- Portability package
- Travel limit switch

SPECIFICATIONS

Model Number	Tilt Capacity	Lowered Height	Platform Size	Standard Motor	Weight
ETT30 SERIES – 30° STANDARD TILT					
ETT30-20	2,000 lb (907 kg)	8" (203 mm)	36" x 48" (914 x 1,219 mm) up to 48" x 60" (1,219 x 1,524 mm)	1 HP	630 lb (286 kg)
ETT30-40	4,000 lb (1,814 kg)				650 lb (295 kg)
ETT30-60	6,000 lb (2,721 kg)			2 HP	690 lb (313 kg)
ETT45 SERIES – 45° STANDARD TILT					
ETT45-20	2,000 lb (907 kg)	8" (203 mm)	36" x 48" (914 x 1,219 mm) up to 48" x 60" (1,219 x 1,524 mm)	1 HP	630 lb (286 kg)
ETT45-40	4,000 lb (1,814 kg)				650 lb (295 kg)
ETT45-60	6,000 lb (2,721 kg)			2 HP	690 lb (313 kg)
ETT90 SERIES – 90° STANDARD TILT					
ETT90-20	2,000 lb (907 kg)	12" (305 mm)	36" x 48" (914 x 1,219 mm) up to 48" x 60" (1,219 x 1,524 mm)	1 HP	630 lb (286 kg)
ETT90-40	4,000 lb (1,814 kg)				650 lb (295 kg)
ETT90-60	6,000 lb (2,721 kg)			2 HP	690 lb (313 kg)



CUSTOM DESIGNS

Engineering and design services are available for unique applications.



Corporate 410 Admiral Blvd Mississauga, ON, Canada L5T 2N6 t 905.457.3900 f 905.457.2313 USA 6350 Burnt Poplar Road Greensboro, NC 27409 www.bluegiant.com

Blue Giant offers a full line of dock levelers, dock safety equipment, seals and shelters, accessories, ergonomic and scissor lift equipment and industrial trucks. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact Blue Giant for latest information. Some features illustrated may be optional in certain market areas.